

*** 보행식 소형 전동 파레트 트럭 Minimover Pedestrian Electric Pallet Truck**

항목	Items	단위	Specification	
			EPT20-15M	EPT20-18M
모델명	Model designation		EPT20-15M	EPT20-18M
최대하중	Load capacity	Q (kg)	1500	1800
하중중심	Load center	c (mm)	600	
휠재질	Tyre type		PU / PU	
주행휠	Tyre size, operator side		Φ252 × 67	
로드휠	Tyre size, load side		Φ73×98(single), Φ84×70(double)	
보조휠	Balance wheels (dimensions)		Φ99.5 × 40	
휠수	Wheels, number operator/load side(x=drive)		1x + 2 / 2	
최저포크높이	Fork height, lowered	h13 (mm)	74 / 85	
전장	Overall length	L1 (mm)	1630	
전폭	Overall width	b1/b2 (mm)	724	
포크제원	Fork dimensions	s/e/l(mm)	44 / 160 / 1000	44 / 160 / 1150
포크외폭	Fork spread, min/STD/max	b5 (mm)	600	685
회전반경	Outer turning radius	Wa (mm)	1400	1550
주행속도	Travel speed, laden/unladen	km/h	3.5 / 4.0	
인상속도	Lifting speed, laden/unladen	m/s	0.056 / 0.060	
하강속도	Lowering speed, laden/unladen	m/s	0.057 / 0.059	
등판능력	Maximum gradeability, laden/unladen S2 5min.	%	5 / 7	
제동장치	Service brake		Electromagnetic	
주행모터	Drive motor rating S2 60min	kW	0.63	
유압모터	Lift motor rating at S3 15%	kW	0.8	0.84
배터리용량	Battery voltage/rated capacity (5h)	V/Ah	24 / 70	24 / 85
배터리형식	Battery type		Maintenance free battery	
제어장치	Type of drive control / Manufacturer		DC / CURTIS	
작동소음	Sound level at operator's ear	dB(A)	70	

EPT20-15M / 18M



Easy Control Handle



Display Unit (BDI)



Lowest Fork Height



Solid Steel Frame



Minimum Turning Radius



Stability & Safety

