

*** 보행식 전동 파레트 트럭 Pedestrian Electric Pallet Truck EPT20-20WA**

항목	Items	단위	Specifications
최대하중	Load capacity	Q (kg)	2000
하중중심	Load center	c (mm)	600
자중(배터리포함)	Service Weight(Incl. battery)	kg	535
휠재질	Wheel type		PU / PU
주행휠	Wheel size, operator side		Φ230×75
로드휠	Wheel size, load side (double)		2×Φ85×70 / Φ85×115
보조휠	Balance wheels (dimensions)		Φ85×48
휠수	Wheels, number operator/load side (x=drive)		1x+2 / 2 or 4
인상거리	Lift height	h3 (mm)	125
최저포크높이	Fork height, lowered	h13 (mm)	85
전장	Overall length	L1 (mm)	1748 / 1818
전폭	Overall width	b1/b2 (mm)	710
포크제원	Fork dimensions	s/e/l(mm)	55/150/1150 55/170/1220
포크외폭	Fork spread, min/max	b5 (mm)	540 / 685
회전반경	Outer turning radius	Wa (mm)	1638 1659
주행속도	Travel speed, laden/unladen	km/h	5.0 / 5.5
등판능력	Maximum gradeability, laden/unladen S2 5min.	%	8 / 16
제동장치	Service brake		Electromagnetic
주행모터	Drive motor rating S2 60min	kW	1.10
유압모터	Lift motor rating at S3 15%	kW	0.84
배터리용량	Battery voltage/rated capacity (5h)	V/Ah	24 / 210
제어장치	Type of drive control / Manufacturer		AC / ZAPI
작동소음	Sound level at operator's ear	dB(A)	74

*** AC Technology System**



*** 견고한 프레임**



*** 내구성 AC Drive System**



*** 고효율 Tiller Head**



*** 공간활용의 저속기능**



*** 최소화전반경**

