

* 경제형 보행식 전동스태커 Economical 1.0 ton Electric Stacker ES10-10M/22M

항목	Items	단위	Specification
최대하중	Load capacity	Q (kg)	1000
하중중심	Load center	c (mm)	600
자중(배터리포함)	Service Weight(Incl. battery)	kg	475 / 625
휠재질	Tyre type		PU
주행휠	Tyre size, operator side	mm	Φ210×70
로드휠	Tyre size, load side (double)	mm	Φ80×60 / Φ100×50
보조휠	Balance wheels (dimensions)	mm	Φ130×55 / Φ100×50
휠수	Wheels, number operator/load side(x=drive)		1x + 2 / 4
전고(Mast 최저)	Height, mast lowered	h1 (mm)	1940
최대양고	Lift height	h3 (mm)	1600
최저포크높이	Fork height, lowered	h13 (mm)	85 / 50
전장	Overall length	L1 (mm)	1615 / 1570
전폭	Overall width	b1/b2 (mm)	800 / 1135~1435
포크제원	Fork dimensions	s/e/l(mm)	60×170×1150 / 35×100×1070
포크외폭	Outside Fork width	b5 (mm)	550 / 200~700
최저지상고	Ground clearance,	m2 (mm)	30 / 40
회전반경	Outer turning radius	Wa (mm)	1295 / 1329
주행속도	Travel speed, laden - unladen	km/h	3.5 - 4.0
인상속도	Lifting speed, laden - unladen	m/s	0.12 - 0.22
하강속도	Lowering speed, laden - unladen	m/s	0.12 - 0.11
등판능력	Maximum gradeability, laden - unladen S2 5min.	%	3 - 6
제동장치	Service brake		Electromagnetic
주행모터	Drive motor rating S2 60min	kW	0.65
유압모터	Lift motor rating at S3 15%	kW	2.2
배터리용량	Battery voltage/rated capacity (5h)	V/Ah	2 × 12 / 60
배터리형식	Battery type		Gel Battery
제어장치	Type of drive control / Manufacturer		DC / CURTIS
작동소음	Sound level at operator's ear	dB(A)	74

ES10-10M / 22M



* 효율적인 틸러손잡이



* 집약적 계기판



* 부드러운 조향핸들



* 컴팩트 디자인



* 내장형 단상 충전기

