

* 보행식 전동 파레트 트럭 Pedestrian Electric Pallet Truck

항 목	Items	단위	Specification
모델명	Model designation		WP17-15
최대하중	Load capacity	Q (kg)	1500
하중중심	Load center	c (mm)	600
휠재질	Tyre type		PU / PU
주행휠	Tyre size, operator side		Φ252 × 67
로드휠	Tyre size, load side		Φ84×70 (double)
보조휠	Balance wheels (dimensions)		None
휠수	Wheels, number operator/load side(x=drive)		1x / 4
최저포크높이	Fork height, lowered	h13 (mm)	85
전장	Overall length	L1 (mm)	1707
전폭	Overall width	b1/b2 (mm)	697
포크제원	Fork dimensions	s/e/l(mm)	55 / 160 / 1150
포크외폭	Fork spread, min/STD/max	b5 (mm)	685
회전반경	Outer turning radius	Wa (mm)	1547
주행속도	Travel speed, laden/unladen	km/h	3.0 / 3.5
인상속도	Lifting speed, laden/unladen	m/s	0.056 / 0.060
하강속도	Lowering speed, laden/unladen	m/s	0.057 / 0.059
등판능력	Maximum gradeability, laden/unladen S2 5min.	%	5 / 7
제동장치	Service brake		Electromagnetic
주행모터	Drive motor rating S2 60min	kW	0.63
유압모터	Lift motor rating at S3 15%	kW	0.8
배터리용량	Battery voltage/rated capacity (5h)	V/Ah	2 × 12 / 85
배터리형식	Battery type		Maintenance free battery
제어장치	Type of drive control / Manufacturer		DC / CURTIS
작동소음	Sound level at operator's ear	dB(A)	70

WP17-15



Easy Control Handle



Display Unit (BDI)



Steel Cover



One Piece Fork Frame



Integrated Component



Motor Cooling Fan

