

*** 보행식 전동 카운터 스택커 Counter Balance Electric Stacker XEP07**

항 목	Items	단 위	Specifications
허용하중	Load capacity	Q(kg)	700 (500)
하중중심	Load center	C(mm)	400
자중	Weight (without battery)	kg	900 / 1000 / 1200
휠종류	Tyres		Polyurethane
주행휠크기	Driving wheel size	b3(mm)	Φ220
로드휠크기	Loading wheel size	b2(mm)	Φ210
전장	Overall length	L1(mm)	1880
전폭	Overall width	b1(mm)	700
전고(마스트최저)	Lowered mast height	h1(mm)	2090 / 1750 / 2000
전고(마스트최고)	Extended mast height	h4(mm)	2090 / 3050 / 3550
포크최저고	Forks height,lowered	b6(mm)	70
포크길이	Forks length	Shell(mm)	800
최대양고	Lift height	h3(mm)	1600 / 2500 / 3000
최저지상고	Minimum ground clearance	b7(mm)	40
최소회전반경	Turning radius	Wa(mm)	1150
주행속도	Travel speed, loaded/unloaded	km/h	2.5 / 3.0
인상속도	Lift speed, loaded/unloaded	mm/s	75 / 105
하강속도	Lowering speed, loaded/unloaded	mm/s	145 / 80
등판능력	Max gradeability, loaded/unloaded	%	5 / 8
제동장치	Service brake		Electromagnetic brake
주행모터	Drive motor rating	kw	0.5
유압모터	Lift motor rating	kw	1.6
배터리용량	Battery voltage / nominal capacity	V/Ah	12 / 80 × 2
제어장치	Type of drive control		MOSFET control
작동소음	Noise level at operator's ear	dB(A)	< 70



XEP07 M1.6

- * Easy tiller head
- * Wide view & Tilting mast
- * Durable Steel Frame
- * Light Service Weight
- * Economical Parts System
- * Easy Maintenance

www.ep-ep.co.kr
 이피 이클먼트 코리아(주)
 EP Equipment Korea Co., LTD
 TEL : 031-925-4100 FAX : 031-925-4102