

\* 보행식 전동 카운터 스택어 Counter Balance Electric Stacker XEP10

항 목	Items	단 위	Specifications
허용하중	Load capacity	Q(kg)	1000
하중중심	Load center	C(mm)	500
자중	Weight (without battery)	kg	1329
휠종류	Tyres		Polyurethane
주행휠크기	Driving wheel size	mm	Φ250×80
로드휠크기	Loading wheel size	mm	Φ210×85
전장	Overall length	L(mm)	2400
전폭	Overall width	W(mm)	850
전고(마스트 최저)	Lowered mast height	H(mm)	1980/2180/1700/1800/1950/2100
전고(마스트 최고)	Extended mast height	H4(mm)	2557/2757/3430/3630/3930/4230
포크최저고	Forks height, lowered	H1(mm)	35
자유인상고	Free lift	H2(mm)	1023/1223/115
최대양고	Lift height	H3(mm)	1600/1800/2500/2700/3000/3300
최저지상고	Minimum ground clearance	H5(mm)	50
최소회전반경	Turning radius	R(mm)	1325
주행속도	Travel speed, loaded/unloaded	km/h	4 / 5
인상속도	Lift speed, loaded/unloaded	mm/s	90 / 120
하강속도	Lowering speed, loaded/unloaded	mm/s	125 / 80
등판능력	Max gradeability, loaded/unloaded	%	5 / 8
제동장치	Service brake		Electromagnetic brake
주행모터	Drive motor rating	kw	1.2
유압모터	Lift motor rating	kw	2.2
배터리용량	Battery voltage / nominal capacity	V/Ah	24 / 210
제어장치	Type of drive control		MOSFET control
작동소음	Noise level at operator's ear	dB(A)	< 70



\* Frei tiller head. Germany



\* Wide view & Tilting mast



\* Sideways battery exit

