

**\* 전동 리치 스택어 Electric Reach Stacker XR15**

항 목	Items	단 위	Specifications
운전방식	Operating type		탑승겸용(Standing on/Pedestrian)
허용하중	Load capacity	Q(kg)	1500
하중중심	Load center	C(mm)	500
휠종류	Tyres		Polyurethane
주행휠크기	Driving wheel size	mm	Φ230×75
로드휠크기	Loading wheel size	mm	Φ210×85
보조휠크기	Balancing wheel size	mm	Φ125×60
휠수	Wheels number, front/rear(x=driven)		1x-2/2
전고(마스트 최저)	Lowered mast height	h1(mm)	1780
자유인상고	Free lift	h2(mm)	90
최대양고	Lift height	h3(mm)	2500
전고(마스트 최고)	Extended mast height	h4(mm)	3440
전장	Overall length	L1(mm)	2090
전폭	Overall width	W(mm)	1090
포크제원	Fork diminsions	s/e/l(mm)	100/35/1070
포크외폭	Fork width	b3	200 ~ 720
리치거리	Reach length	L3	580
최저지상고	Minimum ground clearance	m(mm)	55
통로폭	Aisle width 1000×1200 lengthways	Ast(mm)	2610
최소회전반경	Turning radius	Wa(mm)	1656
주행속도	Travel speed, loaded/unloaded	km/h	4.8 / 5.6
인상속도	Lift speed, loaded/unloaded	mm/s	90 / 120
등판능력	Max gradeability, loaded/unloaded	%	5 / 8
제동장치	Service brake		Electromagnetic brake
주행모터	Drive motor rating	kw	1.2
유압모터	Lift motor rating	kw	2.2
배터리용량	Battery voltage / nominal capacity	V/Ah	24 / 240
제어장치	Type of drive control		MOSFET control
작동소음	Noise level at operator's ear	dB(A)	< 70



Frei tiller ,Germany



Sideways battery exit



Mast Reach & Tilting Fork

